

tesa® 4373 UV

Masking film with special Outdoor Cloth tape

PRODUCT INFORMATION

Product Description

Easy Cover® 4373 UV Extra Strong is a combination of an environment-friendly LDPE film and a UV resistant cloth tape with extra strong adhesion for the masking of large areas in one working step. Product 4373 was especially developed for heavy duty longterm protection outdoors. Once applied it can easily be removed even after 8 weeks of outdoor application without leaving residues. It allows safe and precise fixation on even and slightly rough surfaces. The robust film avoids paint bleeding or leaking to the protected area. The transparency of the film ensures good indoor illumination. 4373 is especially suitable for the masking of large facade parts.

Main Application

It is especially suitable for the masking of windows, balcony balustrades, doors and large facade parts

Technical Data

Backing material

cloth

Elongation at break

10 %

Total thickness

310 µm

Tensile strength

60 N/cm

Thickness of masking coverage

30 µm

UV-resistance

8 weeks

Type of adhesive

natural rubber

Material of masking coverage

LDPE

Adhesion to steel

3.8 N/cm

Properties

Suitable for rough surfaces

Paint anchorage

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit http://l.tesa.com/?ip=04373

Page 1 of 1 / As of 12/15/15

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

tesa tape inc.

Pacific Tes. Ltu. 5825 Carnegie Boulevard Charlotte, N.C. 28209 Singapore 629621 Phone: +1 (704) 554 0707 Fax: +1 (704) 554 0707 Fax: +1 (704) 553 5634 http://www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.