

tesa® 4368

Masking film with slightly creped adhesive paper tape

PRODUCT INFORMATION

Product Description

Easy Cover® 4368 Universal is a combination of an environment-friendly HDPE film and a slightly creped adhesive paper tape for the masking of large areas in one working step. It is resistant against dispersion paints and can easily be removed after short term applications without residues.

Easy Cover 4368 is successfully tested for all standard indoor applications. It allows safe and precise fixation on even surfaces such as skirting boards, window sills, window and door frames. The embossed film avoids paint bleeding or leaking to the protected area. Easy Cover 4368 will achieve a clean paint result with straight paint edges.

Main Application

For base boards, window sills, door and window frames etc.

Technical Data

- Backing material
- slightly-creped paper
- Elongation at break
- 10 %

- Total thickness
- 140 µm
- Tensile strength
- 38 N/cm

- Thickness of masking coverage
- 10 µm
- UV-resistance
- 1 weeks

- Type of adhesive Adhesion to steel
- natural rubber 3.4 N/cm
- Material of masking coverage
- **HDPE**

Properties

- Suitable for sensitive surfaces
- ++
- Sharp colour edge

- Paint anchorage
- ++

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit http://l.tesa.com/?ip=04368

Page 1 of 1 / As of 12/15/15

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

tesa tape inc.

Pacific Test Ltd.

184 Gul Circle,
Singapore 629621
Phone: +1 (704) 554 0707
Pax: +1 (704) 554 0707
Pax: +1 (704) 553 5634
http://www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.