

tesa® 4843

Premium Plastering Tape Orange

PRODUCT INFORMATION

Product Description

tesa® 4843 is a specially formulated plasticised PVC tape with a flat backing, low unwinding force and high adhesion. Having a soft modified and thick rubber adhesive coating tesa® 4843 is suitable for most rough surfaces. The tape can withstand humidity, weak alkaline solutions, acids and many other chemicals. Once applied it can be easily removed even after 2 weeks of outdoor application without leaving any residue.

Main Application

tesa® 4843 is suitable for masking during plastering, painting, gypsum, masonry and stucco work. It protects the surfaces of sensitive profiles and facings against dirt and damage through manufacturing tools and material. It is also suitable for the sealing of bags, heavy duty wrapping and other DIY applications. The tape can be used for temperatures above 0°C.

Technical Data

■ Backing material	PVC film	■ Elongation at break	200 %
■ Total thickness	122 µm	■ Tensile strength	23 N/cm
■ Type of adhesive	natural rubber	■ UV-resistance	2 weeks
■ Adhesion to steel	1.2 N/cm		

Properties

■ Hand tearability	+	■ Sharp colour edge	++
■ Suitable for rough surfaces	++	■ Conformability	++
■ Paint anchorage	+		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04843>

Page 1 of 1 / As of 12/15/15