

tesa® 4364

Masking paper with slightly creped adhesive paper tape

PRODUCT INFORMATION

Product Description

Easy Cover® 4364 is a combination of high quality folded special paper and a slightly creped adhesive paper tape for the masking of large areas in one working step. It is resistant against dispersion paints and can easily be removed after short term applications without

Easy Cover 4364 is successfully tested for all standard in-door applications. It allows safe and precise fixation on even surfaces such as skirting boards, window sills, window and door frames. The masking paper avoids paint bleeding or leaking to the protected area. Easy Cover 4364 will achieve a clean paint result with straight paint edges.

Main Application

For base boards, window sills, door and window frames etc.

Technical Data

- Backing material
- slightly-creped paper
- Elongation at break
- 10 %

- Total thickness
- 140 um
- Tensile strength
- 38 N/cm

- Type of adhesive
- natural rubber
- UV-resistance
- 1 weeks

- Adhesion to steel
- 3.4 N/cm
- Material of masking coverage
- paper

Properties

- Suitable for sensitive surfaces
- ++
- Sharp colour edge

- Paint anchorage
- ++

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit http://l.tesa.com/?ip=04364

Page 1 of 1 / As of 12/15/15

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

tesa tape inc.

Pacific Fe. Ltd.

825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
http://www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.