

tesa® 60099

Fibreglass Tape

PRODUCT INFORMATION

Product Description

tesa® 60099 self-adhesive fibreglass tape features the latest developments in joint tape technology.

With its very strong and flat fibreglass mesh, tesa® 60099 offers durable and long lasting drywall/plaster board joints.

The good adhesion and the very good tensile strength allow one-time application and smooth finished joints.

Main Application

tesa® 60099 is also used for fixing and patching small holes and cracks.

Technical Data

- Backing material
- Total thickness
- Type of adhesive
- fibreglass
- Adhesion to steel
- 0.29 N/cm

- 203 µm
- Elongation at break
- 4.2 %

- acrylic
- Tensile strength
- 134 N/cm

Properties

Conformability

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit http://l.tesa.com/?ip=60099

Page 1 of 1 / As of 12/15/15

tesa SE

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape inc.
5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
http://www.tesatape.com

tesa tape Asia

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.