

tesa® 4613

Utility grade duct tape

PRODUCT INFORMATION

Product Description

tesa® 4613 is a utility grade duct tape. It consists of a 27 mesh woven PET/cotton fabric backing coated with a natural rubber adhesive. tesa® duct 4613 is a self adhesive tape with typical duct features for a wide range of applications.

- good adhesion even on rough surfaces
- easy to tear by hand
- water repellent
- flexible

Main Application

- Sealing of ducts
- Fastening of protection films
- Sealing of rubbish bags
- Fixing, closing, packaging and a lot more!

Technical Data

- Backing material
- PE laminated cloth
- Elongation at break
- 15 %

- Total thickness
- 180 µm
- Tensile strength

- Type of adhesive

- 30 N/cm

- natural rubber
- Temperature resistance (30 min)
- 95 °C

- Adhesion to steel
- 4.1 N/cm
- Mesh

27 count per square inch

Properties

- Hand tearability Straight tear edges
- 0
- Abrasion resistance Water resistance
- 0

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit http://l.tesa.com/?ip=04613

Page 1 of 1 / As of 12/15/15

tesa SE

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape inc.

Pacific Tes. Ltu. 5825 Carnegie Boulevard Charlotte, N.C. 28209 Singapore 629621 Phone: +1 (704) 554 0707 Fax: +1 (704) 554 0707 Fax: +1 (704) 553 5634 http://www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.