

## tesa® 4334 Precision Mask®

High grade paper masking tape for precise and flat paint edges

### PRODUCT INFORMATION

#### Product Description

tesa® 4334 Precision Mask® consists of an extra-thin and strong paper backing coated with an acrylic adhesive.

The combination of the highly equipped backing material and the outstanding special adhesive formulation allows easy removability up to 5 months after application, with 4 weeks of UV resistance. This enables multiple working processes in only one covering process.

#### Main Application

This tape is suited for almost all indoor paint works.

tesa® 4334 Precision Mask® is applicable with water-based paints and lacquers and fits even for high-class spatula techniques.

It is suitable for a variety of common surfaces such as glass, aluminium, hard-PVC and wood.

It is especially suited for indoor applications when a precise razor-sharp paint edge is needed.

#### Technical Data

|                    |            |                       |           |
|--------------------|------------|-----------------------|-----------|
| ■ Backing material | flat paper | ■ Adhesion to steel   | 1.85 N/cm |
| ■ Total thickness  | 90 µm      | ■ Elongation at break | 4 %       |
| ■ Type of adhesive | acrylic    | ■ Tensile strength    | 30 N/cm   |

#### Properties

|                                   |    |                     |    |
|-----------------------------------|----|---------------------|----|
| ■ Hand tearability                | ++ | ■ Paint anchorage   | ++ |
| ■ Suitable for sensitive surfaces | +  | ■ Sharp colour edge | ++ |
| ■ Suitable for rough surfaces     | +  | ■ Conformability    | ++ |

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04334>

Page 1 of 1 / As of 12/15/15