

tesa® 4024

Universal carton sealing tape

PRODUCT INFORMATION

Product Description

tesa® 4024 PV 2 is based on a PP backing coated with a special high tack water based acrylic adhesive. The excellent tack of the adhesive secures a good sealing immediately after application.

tesa® 4024 PV 2 has the following additional features:

- · Low noise unwinding.
- Excellent ageing resistance.
- It can be used on all common hand dispensers and machines.

As the product is chlorine free and based on derivatives of mineral oil only, the disposal by heat treatment is environmental friendly.

The process of cardboard waste recycling will be not disrupted as confirmed by leading recycling companies and paper mills.

Main Application

Manual and automatic sealing of light and medium-range weight cartons.

Technical Data

- Backing material
- PP film
- Adhesion to steel
- 3 N/cm

- Total thickness
- 52 µm
- Elongation at break
- 140 %

- Type of adhesive
- acrylic
- Tensile strength
- 45 N/cm

Properties

- Automatic application
- yes
- Printability
- yes

- Manual application
- yes
- Low noise unwinding

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

The PV3-version of the product is printable.

For latest information on this product please visit http://l.tesa.com/?ip=04024

Page 1 of 1 / As of 12/15/15

tesa SE

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape inc.

Pacific Test Ltd.

184 Gul Circle,
Singapore 629621
Phone: +1 (704) 554 0707
Pax: +1 (704) 554 0707
Pax: +1 (704) 553 5634
http://www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.