

# tesa® 4435

**UV Paper Tape** 

PRODUCT INFORMATION

## **Product Description**

tesa® 4435 UV Paper Tape is applicable with all kind of paints. The combination of the conformable backing material and the special adhesive formulation allows easy residue free removability up to 2 weeks after outdoor application. This enables multiple working processes in only one covering process.

## **Main Application**

This tape is suited for almost all outdoor paint works. It is suitable for outdoor applications on a variety of common surfaces.

#### **Technical Data**

- Backing material
- slightly-creped paper
- Elongation at break
- 12 %

- Total thickness
- 145 µm
- Tensile strength
- 38 N/cm

- Type of adhesive
- natural rubber
- UV-resistance
- 2 weeks

2.8 N/cm Adhesion to steel

# **Properties**

Hand tearability

Suitable for rough surfaces

- Paint anchorage Conformability

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

#### **Additional Info**

The application of an adhesive tape on weathered surfaces may lead to residues during the de-masking. Therefore we strongly recommend a test application before.

For latest information on this product please visit http://l.tesa.com/?ip=04435

Page 1 of 1 / As of 12/15/15

tesa SE

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape inc.

Pacific Fe. Ltd.

825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
http://www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.